

Available Overshots with Spiral Grapples for fishing given diameters.

Max. Catch T.J. or D.C. O.D.	Overshot O.D. (inches)	SPIRAL GRAPPLE			
		Grapple No.	Type	Bowl No.	Load Capacity (lb.)
3 1/8	3 7/8	B-1837	SH	B-1836	155,100
	4	B-5109	SH	B-5106	262,900
	4 1/8	1741	FS	9107	310,200
	4 1/8	1741	FS	8223	310,200
	4 1/8	M-1741	FS	M-9107	255,000
	4 1/4	B-791	FS	B-4824	291,800
3 7/8	4 5/8	B-6234	SH	B-6232	186,800
	4 3/4	B-1709	SH	B-5141	370,000
	5 3/8	B-2489	SH	B-5167	297,000
	5 1/4	859	FS	9517	451,000
4 7/8	5 3/4	B-6389	SH	B-7098	273,500
	6	9022	FS	9028	405,000
	6 1/8	1182	FS	905	405,000
	6 3/8	1182	FS	3075	558,000
	6 5/8	8619	SH	8617	386,000
	6 5/8	9213	SH	9,211	444,000
5 1/4	7 1/2	220	FS	9998	590,000
	7 5/8	220	FS	249	670,000
	7 5/8	220	FS	B-3366	637,500
	7 5/8	220	FS	7574	611,300
6 1/4	7 3/8	9687	SH	12568	471,000
	7 3/8	9687	SH	9694	450,400
	7 3/8	9687	SH	12566	471,000
	7 3/8	B-4694	SH	B-4693	414,100
	7 3/8	M-9687	SH	M-9694	467,600
	7 5/8	1644	SFS	1641	502,100
	7 5/8	1644	SFS	1875	542,468
	7 5/8	1644	SFS	19092	542,500
	7 5/8	M-1644	SFS	M-1641	542,468
	7 7/8	1659	FS	1657	627,600
	7 7/8	M-1659	FS	M-1657	645,300
	7 7/8	1659	FS	9749	655,000
	7 7/8	1659	FS	9984	655,000
	7 7/8	B-2073	FS	B-2109	586,800
6 1/2	7 7/8	B-2073	FS	C-2205	640,000
	7 5/8	B-5349	SG	B-5346	430,000
	7 5/8	9863	SH	9862	418,200
	8 1/8	9863	FS	9748	420,000
	8 1/8	B-2374	FS	B-3711	586,500
	8 1/4	5652	FS	2382	760,000
6 5/8	8 1/4	5652	FS	7797	760,000
	7 3/4	9137	SH	9134	422,000
	7 3/4	M-9137	SH	M-9134	345,000
	7 3/4	M-9137	SH	B-11323	345,000
	7 3/4	B-5219	SH	B-5216	350,000
	8 1/8	84	SFS	9337	590,000
	8 1/8	M-84	SFS	M-9337	587,000
6 3/4	8 1/4	N-84	FS	B-3034	637,500
	7 7/8	B-5227	SH	16502	413,000
	8 1/8	B-5227	SH	B-5224	531,900
	8 3/8	209	FS	277	637,000
7	8 3/8	M-209	FS	B-3816	612,199
	8 1/8	9222	SH	9817	453,000
	8 1/8	9222	SH	9219	453,000
	8 1/8	B-3267	SH	B-3264	439,200
	8 3/8	9222	SH	17209	587,977
	8 5/8	105	FS	7801	637,000
7 1/8	8 5/8	N-105	FS	B-3819	637,000
	8 1/4	9229	SH	9571	422,000
	9 5/8	B-5289	SH	B-5286	419,500
	10 1/8	8957	SH	8962	602,700
8 1/2	10 1/8	M-8957	FS	M-8962	624,300
	10 1/8	B-4430	FS	B-5283	637,000
	10 1/2	8966	FS	8965	296,000
8 3/4	10 1/2	B-5310	FS	B-5307	586,600
	11 1/4	B-12827	FS	B-12824	536,800
9 1/2	11 3/4	15253	FS	15252	966,500

All Strengths listed are calculated theoretical yield points and are accurate within 20%. All strengths assume a straight, steady pull and full grapple engagement of a round fish. Any

FS (Full Strength)-Engineered to withstand all pulling, torsional and jarring strain.
 SFS (Semi Full Strength)-Engineered for special hole condition commensurate with maximum strength.
 SH (Slim Hole)-Engineered to withstand heavy pulling strains only.

When Possible keep 3/8" between Hole OD and WP and 1/4" inside.