

Completion Landing Strings & Intervention Risers

Gas-Tight, Pressure-Rated Rotary Shouldered Connections and an API 17G Qualified Riser

20+ Years of Proven Field History

Size	Connection	TJ ID	Grade	Tool Joints	Pressure Rating
7 5/8"	MaXit™807	6.250"	V-150	130ksi	20,000 psi
7 5/8"	MaXit™807	6.125"	V-150	130ksi	20,000 psi
* 7"	VAM TTR HW-NA	5.300"	VM125SS	125SS	26,560 psi
6 5/8"	TT-M™710	5.625"	V-150	130ksi	20,000 psi
6 5/8"	GT-M™69	5.500"	V-150	130ksi	15,000 psi
6 5/8"	GT-M™69	5.250"	S-135	120ksi	15,000 psi

* Fully qualified API 17G Intervention Riser



Applications:

- Subsea Tubing Landing String
- Flowback / Test String
- Intervention String
- Proven in Open Water Applications

Features:

- Gas-Tight Metal-to-Metal Seal
- Large ID for Completion Plugs
- Slim OD for Work in Drilling Risers
- Internally Coated for Corrosion Prevention
- External Coating Available for Corrosion Prevention

Benefits of a Rotary-Shouldered Connection:

- Compatible with Conventional Drill Pipe Handling Equipment
- Speed of Make-up and Running
- Connections Built for Multiple Make-and-Breaks

Deep Inventory. Even Deeper Expertise.



WORKSTRINGS[™] INTERNATIONAL

A SUPERIOR ENERGY SERVICES COMPANY

For all of our current specification sheets, please visit
<https://workstringsinternational.com/spec-sheets/index.asp>

Global Headquarters

Broussard, LA - USA

Phone: +1 337-989-9675

Email: info@workstrings.com

Engineering & Marketing

Houston, TX - USA

Phone: +1 281-999-0047

Email: marketing@workstrings.com

EMEA Corporate

Aberdeen - UK

Phone: +44 1224-724900

Email: sales.uk@workstrings.com

www.workstringsinternational.com