

7-5/8" MaXit™ 807 Completion Landing String

The Industry's First 7.625" Rotary Shouldered Connection

Size	Connection	Grade	TJ ID	TJ OD
7.625"	MaXit™ 807	V-150	6.125" / 6.250"	9.750"
Tool Joints	Pressure Rating	MUT (ft-lb)	Tensile Strength	
130ksi	20,000 psi	81,739-86,087 80,783-85,130	1.5 MM lbs	



Applications:

- Subsea Tubing Landing String
- Flowback / Test String
- Intervention String

Features:

- Gas-Tight Metal-to-Metal Seal
- Pressure Rating: 20,000 psi
- 6.125" / 6.250" ID for Large Crown Plugs
- Internally Coated for Corrosion Prevention
- External Coating Available (RustGrip®)

Benefits:

- Replaces Casing Connection Landing Strings
- Uses Conventional Drill Pipe Handling Equipment
- Increased Speed of Make-up and Running
- Connections Built for Multiple Make-and-Breaks



Deep Inventory. Even Deeper Expertise.



Scan Code for all of our
current specification sheets

Global Headquarters

1150 Smede Hwy
Broussard, LA 70518 - USA
Phone: +1 337.989.9675
Email: info@workstrings.com

Engineering & Marketing

1001 Louisiana St., Suite 2900
Houston, TX 77002 - USA
Phone: +1 281.999.0047
Email: marketing@workstrings.com

EMEA Corporate

Kirkton Avenue, Dyce
Aberdeen, AB21 0BF - UK
Phone: +44 1224.724900
Email: sales.uk@workstrings.com