

## SPECIFICATION SHEET

### 2 3/8" AC95, 7.70 LBS/FT, PH6 TUBING

#### PIPE BODY DATA

NOMINAL OD (in.)	2 3/8
NOMINAL ID (in.)	1.703
NOMINAL WEIGHT (lbs/ft)	7.70
AVERAGE JOINT WEIGHT (lbs)	239
AVERAGE LENGTH	Range 2
PIPE GRADE	AC95
WALL (in.)	0.336
TUBE DRIFT (in.)	1.609 MIN
NEW PIPE TENSILE YIELD (lbs)	200,000
NEW PIPE TORSIONAL YIELD (ft-lbs)	8,840
NEW PIPE BURST (psi)	15,960
NEW PIPE COLLAPSE (psi)	16,490

#### CONNECTION DATA

CONNECTION	PH6
BOX OD (in.)	3 3/32
UPSET OD (in.)	3 3/32
CONNECTION ID (in.)	1.645
CONNECTION YIELD (lbs)	EXCEEDS PIPE
CONNECTION BURST PRESSURE (psi)	AS PER NEW PIPE
CONNECTION COLLAPSE PRESSURE (psi)	AS PER NEW PIPE
CONNECTION MAKE-UP MINIMUM (ft-lbs)	2,500
CONNECTION MAKE-UP MAXIMUM (ft-lbs)	3,100

**Note:** All used figures have **NO** safety factor included for tension, temperature, or general S.F. etc.

The technical information contained herein, including the product performance sheet and other attached documents, has been extracted from information available from the manufacturer and is for reference only and not a recommendation. The user is fully responsible for the accuracy and suitability of use of the technical information. Workstrings International cannot assume responsibility for the results obtained through the use of this material. No expressed or implied warranty is intended. Drill pipe assembly properties are calculated based on uniform OD and wall thickness. No safety factor is applied. The information provided for various inspection classes and for various wear conditions (remaining body wall) is for information only and does not represent or imply acceptable operation limits. It is the responsibility of the customer and the end user to determine the appropriate performance ratings, acceptable use of the product, maintain safe operational practices, and to apply a prudent safety factor suitable for the application. For API connections that have different pin and box ID's, tool joint ID refers to the pin ID. Per Chapter B, Section 4 VII of the IADC drilling manual,